



- Ancho de impresión de 2"
- Opción USB y Bluetooth o USB y Wifi.
- Práctica, veloz y económica.



Print method	Direct thermal line
Print width	48mm
Dot density	384dot/line
Print speed	60mm/s
Interface	USB+WIFI / USB+Bluetooth / USB+WIFI+Bluetooth
Paper width	58mm
Paper diameter:	50mm
Print commands	Compatible with ESC/POS
Barcode mode	FontB: 9X17dots
	Simplified/Traditional Chinese Character, Japanese, Korean: 24X24dots UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODABAR, ITF, CODE93, COD E128
Data Buffer	4K bytes
NV Flash Buffer	60K bytes
Dimension	148.5*86*58.5mm
Weight	288g (Battery: 98g)
Power adaptor	input: AC220V output: DC8.5V/2A
Lithium battery	1900mAh/7.4V
Charge period	2.5h-3h
Work environment	Temperature: 5~45°C, Humidity: 10~80%
Storage environment	Temperature: -10~50°C, Humidity: 10~90%
Mechanism Reliability	50KM
Others	Driver Android, iOS, (Win9X/Win ME/Win2000/WinNT/WinXP, WinVista, Win7, Win 8, Linux)
Paper supply method	Drop-in paper load

